

Alcohol resistant / Aqueous film-forming - AR-AFFF general-purpose foam concentrate for hydrocarbons and polar solvent fires at 6%

Product description

HYDRAL AR 6-6 is a synthetic foam concentrate based on surfactant, fluorosurfactant, polymer and fluoropolymer. The foam forms a film of water on hydrocarbons and in addition a polymer film on polar solvents.

HYDRAL AR 6-6, alcohol resistant and aqueous film forming foam (AFFF) concentrate, is ideally suitable for extinguishing fires involving polar and/or foam-destroying liquids such as alcohols, esters, ketones, amines and also hydrocarbon fires involving petrol, fuel or oil.

Performances

For fires involving foam-destroying liquids we recommend a proportioning rate of 6% (v/v) of **HYDRAL AR 6-6** and a gentle indirect application of the foam, for example using foam deflectors so that the polymer film can become fully effective.

HYDRAL AR 6-6 is especially suitable to extinguish rapidly large surface hydrocarbon fires; the foam has excellent flow properties at a proportioning rate of 6% (v/v) and can be applied direct to the fire surface.

HYDRAL AR 6-6 can be used by most conventional foam equipment such as:

- Balance pressure pump proportioning equipment
- Bladder tank and related proportioners
- Around-the-pump proportioners
- Fixed and portable In-line venturi type inductor
- Fixed or handline nozzles with fixed induction/pick up tubes

Application

HYDRAL AR 6-6 is used wherever storage conditions does not require a high freeze protection such as most of the fixed fire extinguishing installations. Examples for its use are in Bladder tanks proportioning systems, and is frequently used on Jetties, tank farms, chemical process and any flammable liquid storage installations.

HYDRAL AR 6-6 is also very effective when subsurface injection is used to fight tank fires. Due to its fluorinated surfactants content the foam absorbs only small quantities of hydrocarbons.

HYDRAL AR 6-6 is compatible with all foam-compatible dry chemical extinguishing powders.

Sea water can be used without an increase in the application rate.



Storage and shelf life

HYDRAL AR 6-6 has an operational temperature range of 0°C and +50°C. Limited exposure to temperatures above +50°C does not affect the firefighting performance.

When stored in the packaging supplied (polyethylene drums or cans) or in equipment recommended by the manufacturer as part of the foam system and within the temperature limits specified, the shelf life of **HYDRAL AR 6-6** Concentrate is about 20-25 years.

The factors affecting shelf life and stability for HYDRAL AR-AFFF Agents are discussed in detail in our Technical Bulletin for storage recommendation.

If the product is frozen during storage or transportation, the concentrate should be thawed and used without any degeneration of the performance.

Safety and handling

See our corresponding "Material Safety data sheet".

Materials of Constructions Compatibility

Tests have been performed with HYDRAL Concentrate verifying its compatibility with standard carbon steel "black" pipe and pipe manufactured from various stainless steel or brass compounds.

Alternative pipe, fittings, and valves may be used in some cases if acceptable to the customer and/or the authority having jurisdiction.

Refer to our Technical Bulletin, addressing acceptable materials of construction for use with HYDRAL foam concentrates.

Galvanized pipe and fittings must not be used in areas where undiluted concentrate will contact them since corrosion will result.

Please first consult Tyco for specific guidelines concerning materials of construction.

Quality insurance

HYDRAL AR 6-6 – as with all TYCO Products – is subject to a very stringent quality controls throughout all stages of production, from incoming raw to the complete product and is manufactured in an ISO 9001:2000 controlled facility. Quality assurance is therefore guaranteed.

Typical properties

HYDRAL AR 6-6	AR-AFFF
Fire Classes	A and B
Shape and color	Pale yellow clear liquid
Smell	Characteristic, surfactant-alike
Density (20°C)	1,03 ±0.02 [g/ml]
pH (concentrate, 20°C)	7,5 ±0.5
Viscosity 20°C (*)	1200 ±200 [Cps]
Sediment (EN 1568)	≤ 0,1 [%]
Admixing ratio	6 [% Vol.]
Expansion Ratio (EN 1568-3)	≥ 8,0
Drain Time 25%, (20°C, EN 1568-3)	≥ 10:00 [min:s]
Drain Time 50%, (20°C, EN 1568-3)	≥ 15:00 [min:s]
Expansion	Low, Medium, (High)
Freezing Point	≤ -5[°C]
Pour Point	≤ -3 [°C]
Recommended storage/Usage temperature	0 to +50 [°C]
* Brookfield speed 60 rpm, spindle #3	

Ordering information

HYDRAL AR 6-6 can be supplied in cans, drums or totes.

Part No. F116320C1	25 Liter can
Part No. F116320D1	200 Liter drum
Part No. F116320T1	1000 Liter tote