

PLUREX MD3 Foam Concentrate

Multi-purpose freeze protected high expansion foam concentrate to be proportioned at 3% (freeze protected to minus 15°C)

Description

PLUREX MD3 is a synthetic multipurpose foam concentrate based upon fatty alcohols, alkyl sulphates and butyl carbitol. Many fire tests during test programs have shown that it forms stable foam blanket on burning non-polar solvents. It also forms stable low, medium and high expansion foam which rapidly fills large spaces.

PLUREX MD3 foam Concentrate can be used to produce foam with expansion ratios ranging from 50:1 to 1000:1 depending upon the type of generator and its operating pressure. When used with High-Expansion or Medium Expansion Generators, recommended proportioning is at 3% (3 litre of PLUREX MD3 with 97 litres water).

Performance

The performance of PLUREX MD3 foam concentrate when used at high expansion will vary depending upon the performance characteristics of the equipment. Expansion ratios through high expansion generators typically are between 200:1 and 1000:1. For this reason, it is important for the proper design of a high expansion system that the PLUREX MD3 foam Concentrate be specifically tested with the foam generators.

Medium expansion foam generators typically deliver expansion ratios between 50:1 and 200:1.

PLUREX MD3 can be used by most conventional foam equipment such as:

- Balance pressure pump proportioning equipment
- Bladder tank and related proportioners
- Around-the-pump proportioners
- Fixed and portable In-line venturi type inductors
- Fixed or handline nozzles with fixed induction/pick up tubes



Application

PLUREX MD3 is a multi-purpose firefighting agent, used in fighting Class A and Class B both indoors and outdoors. It is used only with air aspirating foam discharge devices except when used as a wetting agent on Class A fuels.

When used with high expansion generators, PLUREX MD3 is capable of totally flooding large rooms and enclosures allowing it to effectively extinguish horizontal and vertical (three-dimensional) fires. High expansion foam is also effective in reducing vapour concentrations downwind from hazardous low boiling point gaseous products such as ammonia spills.

When used with medium expansion foam equipment, PLUREX MD3 forms a foam blanket which prevents the release of fuel vapour and also provides additional cooling due to the higher water content. Medium expansion foam has benefits in outdoor applications because the foam is less affected by wind conditions.

PLUREX MD3 is ideal for fixed medium and/or high expansion system, Fire Brigades, aircraft hangars.

The foam produced by PLUREX MD3 extinguishes hydrocarbon fires best when applied by gentle application. PLUREX MD3 is compatible with all foam-compatible dry chemical extinguishing powders.

Sea water can be used without an increase in the application rate.

Approvals

PLUREX MD3 is tested and approved according to:

- EN 1568: 2008 Part. 1
- EN 1568: 2008 Part. 2
- EN 1568: 2008 Part. 3
- OKF - TVL (Hungary)



Storage and Shelf Life

PLUREX MD3 has an operational temperature range of -12°C and +60°C. Limited exposure to temperatures above +60°C does not affect the firefighting performance.

When stored in the packaging supplied (polyethylene drums or cans) or in equipment recommended by the manufacturer as part of the foam system and within the temperature limits specified, the shelf life of PLUREX MD3 concentrate is about 20-25 years.

The factors affecting shelf life and stability for SABOFOAM agents are discussed in detail in our Technical Bulletin for storage recommendation.

If the product is frozen during storage or transportation, the concentrate should be thawed and used without any degeneration of the performance. For more information, please email at: sabofoam.levate@tycoint.com

Eco-Toxicology and Disposal

PLUREX MD3 is environmentally safe and rapidly biodegradable.

Safety and Handling

See our corresponding "Material Safety data sheet".

Quality Assurance

PLUREX MD3 – as with all TYCO Products – is subject to very stringent quality controls throughout all stages of production, from incoming raw to the complete product and is manufactured in an ISO 9001:2008 controlled facility. Quality assurance is therefore guaranteed.

Typical Properties

■ PLUREX MD3	Multi-purpose Hi-ex foam
■ Fire Classes	A and B
■ Shape and colour	Pale yellow clear liquid
■ Smell	Characteristic, surfactant-alike
■ Density (20°C)	1.03 ±0.02 [g/ml]
■ pH (concentrate, 20°C)	7.0 ±0.5
■ Viscosity 20°C	8.0 ±2.0 [mm ² /s]
■ Sediment (EN 1568)	0.1 [%]
■ Admixing ratio	3 [% Vol.]
■ Expansion Ratio (EN 1568-3)	9.0
■ Drain Time 25%, (20°C, EN 1568-3)	8:00 [min:s]
■ Drain Time 50%, (20°C, EN 1568-3)	13:00 [min:s]
■ Expansion	Low, Medium, High
■ Freezing Point	-17 [°C]
■ Pour Point	-15 [°C]
■ Recommended storage/ Usage temperature	-12 to +60 [°C]

Ordering Information

PLUREX MD3 can be supplied in cans, drums, totes or Bulk (contact us for Bulk delivery details).

<u>Part No.</u>	<u>Description</u>
■ F203331C2	20 Litre can
■ F203331C1	25 Litre can
■ F203331D1	200 Litre drum
■ F203331T1	1000 Litre tote

www.sabofoam.com